ANGLE-SHOE NYLON pivot hinges for 35mm doors


PAS.35
'Angle-Shoe'
Nylon pivots


Angle-Shoe Pivots 25A 43-51 Giles St Kingston ACT 2604

Australia 61 2 6232 6455

MADE IN CANBERRA AUSTRALIA







APPLICATIONS

- 35mm doors to 35kg (1 3/8" 70 lbs) 'invisible' doors in sheetrock
- · bedrooms, bathrooms, robes, coat, linen & laundry closets
- · internal joinery, room dividers, screens, laundry chutes
- · external shutters, louvre blades, ventilators & access panels

LOAD CAPACITY

- 35Kg tested to 500,000 cycles (90° open/close)
- · ideal for hollow core or semi-solid doors to 35kg
- maximum door size 2400 high 1000 wide 36 thick

ADVANTAGES

- · simple hand tool installation without special trade skills
- non-handed universal semi-concealed pivot hinge set
- · door frames and architrave trim can be eliminated
- painting work reduced to roller work (cutting-in eliminated)
- · latch & lever can be eliminated no hinge knuckles

PIVOT SET MATERIAL & FINISHES

- Nylon pivot set (top & bottom pivots are the same)
- · Nylon parts polyamide/molybdenum di-sulphide blend
- Nylon finish dark charcoal grey (can be painted)
 - etch prime + epoxy or auto spray cans
- Rivet material bronze (copper alloy)

NOTES FOR DESIGNERS & SPECIFIERS

- · provides simple durable longevity for light timber doors
- pivots are riveted together and do not come apart
- · detail with care prototype for a full understanding
- plumb & square openings required for set-plaster work
- 870mm wide doors between rooms (820 for bathrooms) 870 doors = 786mm open width for furniture access 820 doors = 736mm open width for bathrooms
- pivot doors do not swing open 180°
- pivot stile swings 'in' 53mm when the door opens 'out'
- Moly-Poly blend included for UV resistance & lubrication

ANGLE-SHOE PRODUCTS

angleshoe.com.au

Unit 25A 43-51 Giles St. Kingston ACT 2604 AUSTRALIA Email - hstyles@bigpond.net.au Tel (02) 6232 6455

