

# 18 40 40 12.5 m8 threaded rod 12.5 o 12.5 o

Halliday + Baillie brackets are tested in accordance with both the AS/NZS 1170.1:2002 (Structural Design Actions) standards and the International Building Code, IBC (2003) to comply with the 200lb fall rating.

Designed and manufactured in New Zealand. For more information, installation templates, and measured drawings of this product and others please visit: www.hallidaybaillie.com or contact your authorized Halliday + Baillie dealer. All information subject to change.

## <u>hallid</u>ay baillie

# HB 520

### STAIR RAIL BRACKET

The Halliday + Baillie HB 520 Stair Rail Bracket provides a crisp option for 30–50mm diameter timber rails.

Suitable for interior or covered exterior situations. For exterior or marine environments, please specify the HB 530 bracket in marine grade 316 stainless steel.

Projection from wall (offstand): 100mm Overall height (upstand): 65mm

Includes all fasteners. Epoxy required for installation, not included (please contact your local H+B dealer for further information).

Material : non-anodized aluminum alloy Recommended Spacing : 600-800mm

Available in all standard finishes except "BN" Brushed Nickel. See finishes sheet for further details.





# HB 522

### GLASS FIXING KIT FOR HB 520 BRACKET

Suitable for 10-15mm glass thickness.

Finishes to match the HB 520 Bracket.

Glass fixing kits sold separately (used in conjunction with the bracket, and not as a replacement).

