3 Lever Mortice



3 Lever Horizontal Mortice Lock

2077

Application:

- For timber doors hinged on the left or right
- Keys suitable for use on doors up to 54mm thick

Operation:

- · Deadbolt locked or unlocked by key from either side
- Latch bolt withdrawn by knob or sprung lever handle from either side
- Two way action, suitable for knobs or sprung lever handles (not suitable for unsprung lever handles)
- · Pierced to accept bolt through furniture
- May be keyed alike with 2157, 2177, 2277 & 2477

Specification:

Reference 2077

Case Size 124mm (5") or 149mm (6")

Backset 38mm or 51mm

Case Steel, silver powder coat
Forend Stainless steel or brass
Striking Plate Finished to match forend

Deadbolt Brass, with hardened steel rollers

Latch BoltBrass, easily reversibleFollower8mm square. Two way actionRebate Kit2939 (13mm, 19mm or 25mm)

Keying Groups May be supplied to pass.

Supplied with 2 steel nickel plated

keys

Key Blank Number KB436

Keying 100 standard differs

(numbers from M101M to M200M)

NB: Not suitable for master keying



Features:

- Reversible latch bolt
- · Available with square forend and striking plate

Finishes:

- SC Satin Chrome finish
- · PL Polished Brass finish

Standards:



 EN 1634-1 assessed for use on 60 minutes timber fire doors

Ordering Code Example:

J 2077 - PL - 6.00

(Boxed - Product Code - Finish - Case Size)

Y 2077 - PL - 6.00

(Visi Packed - Product Code - Finish - Case Size)

